

Water/ Methanol Injection Highest Pressure Diaphragm Pump





SFeatures:

- Self-priming high-pressure diaphragm pump
- Air-free design ensures smooth, pulsation-free flow
- Adjustable pressure: 300 PSI (13.8 bar)
- Flow rate: 2500 cc/min (150 LPH / 40 GPH)
- Voltage range: 36V
- Nominal current: 2.7A, Max current: 10.8A
- Constructed from durable HDPE/ABS plastic, rubber, and steel
- 100% methanol compatible suitable for all alcohol/water mixtures
- No pressure cut-off switch → prevents oscillation and pressure spikes
- Internal bypass provides steady, constant flow
- Large female ports
- Low RPM motor design (as low as 60 RPM) ensures long lifespan
- Can safely operate dry for up to one hour
- Can accept a **50Hz PWM signal** for flow control

Instructions / Safety Notes

- 1. All components pump, lines, fittings, filler, flow sensor, tank, and nozzles are **100%** methanol compatible.
- 2. **Methanol Resistance:** Equipped with **EPDM seals** for improved resistance against methanol degradation.
- 3. **Electrical Supply:** Ensure stable power between **36V** with proper fuse protection.

⚠ Application Note

- 1. **Operating Precaution:** The pump may run dry for a short period (up to 1 hour), but continuous dry operation should be avoided.
- 2. Safety Limit: Do not exceed 50% methanol concentration.

Box Contents

- 1. High-Pressure Diaphragm Pump
- 2. Product Stickers
- 3. Installation Manual

Natallation Guide

- If no transfer pump is used → mount the injection pump below the tank in the luggage compartment.
- If transfer pump is used → injection pump can be mounted in the engine bay.
- Although the pump is self-priming, we recommend positioning the pump inlet below the fluid level of the tank, as vehicle movement and vibrations during driving may cause air to enter the suction line.

□ Electrical Connections

Color Function Section (mm²) Length

Red Positive 1 30 cm Black Negative 1 30 cm

▲ Instructions

Disclaimer: PRODIMAR LTD assumes no responsibility for any **engine damage or personal injury** resulting from improper installation or handling of methanol. Handle methanol with care — it is **toxic and highly flammable.**

Warranty

All Bosphorus Innovations products are covered by a 2-year warranty against manufacturing defects, valid from the date of delivery.

Follow Us

Social Media:

https://www.instagram.com/bosphorus_innovations

https://www.facebook.com/BosphorusInnovations

https://www.youtube.com/channel/UCzbN5CcDePwMBclBiBJGrbw/videos

https://g.page/BosphorusInnovations/

Online Stores:

https://www.bosphorusinnovations.com/shop

https://www.ebay.com/usr/hlyaer_0

https://www.amazon.com/shops/bosphorusinnovations

https://www.facebook.com/pg/BosphorusInnovations/shop/

https://tr1061054643.fm.alibaba.com/

https://www.ptttrade.com/company/bosphorus-innovations

https://bosphorusinnovations.aliexpress.com/

P Company Info

Bosphorus Innovations

Headquarter

Prodimar iç ve Dış Tic. Elektronik San. Ltd. Şti.

Maltepe Street Alba Site No:12BI, Bayrampasa, Istanbul, TURKIYE

Warehouse

3260 Gorham Ave Suite 5954 Minneapolis, MN 55426, USA

Phone: +90 212 544 3141 / +01 952 232 0677

■ WhatsApp: +90 850 307 5458

■ GSM: +90 535 942 8747

Email: info@bosphorusinnovations.com

Web: www.bosphorusinnovations.com

